



LCO/350H/TD1G



LCO/425H/TD1G



LCO/1000V/TD1G



# Multi-Purpose Large Capacity Ovens

The Genlab Large Capacity Oven Range combines precision engineering with exceptional efficiency and reliability, delivering the perfect solution for larger scale warming, drying and heat treatment processes as well as general laboratory applications.

Designed with our latest intuitive touchscreen control system, these incubators offer effortless operation and outstanding temperature accuracy - ensuring consistent results every time.

For added versatility, the LCO range offers optional temperature and energy data recording, along with optional variable fan speed control (50-100%).

Engineered for performance and built to last, Genlab Large Capacity Ovens bring innovation, accuracy, and value together in one advanced system.

## Features

- 8 sizes (250 to 1000 litres - single door design)
- 9 sizes (250 to 1250 litres - twin door design)
- Temperature range 50°C to 250°C
- On screen historical trending (48 hours)
- 8 stage profile control
- Countdown timer
- 24/7 real time clock operation
- Manual or automatic overheat reset
- High accuracy PT100B duplex sensors <0.8°C
- Fan assisted circulation
- Excellent stability
- Low chamber uniformity
- Energy efficient with integral energy meter
- New - set point lock feature
- Selectable HMI languages 

## Options

- Integral Temperature Logger with reporting firmware
- 10 menu x 8 stage profile (& cyclic control)
- Stainless steel chamber
- Audible warnings
- Explosion relief panels
- Access ports (25, 50, 75 or 100mm)
- Traceable calibration to national standards
- Bespoke stands and stacking kits
- Extractor unit
- Extended warranty
- Bespoke solutions available upon request
- Castor wheels (fitted as standard above 425L versions)
- 3 phase upgrade for quicker response (standard above 600L versions)
- Fan speed control (50-100%)



## Design



The exterior is constructed from sheet steel and finished in an easy clean powder coated paint. The interior chamber is made from mild steel coated with aluminium (CLAD) with a stainless steel chamber available as an option. Fitted with fixed shelf runners and removable chrome plated wire grid shelves. The vertical style units are fitted with single doors, the horizontal style units are fitted with twin doors.

## Heating

Heated by Incoloy sheathed elements positioned in the side fan duct for all units except the 250H and 350H, which have a base fan duct.

## Controls

The control system comprises of a bespoke touch screen user interface that offers both accurate temperature control and an integral overheat system by using 2 individual PT100 sensors. Advanced features can be turned on and off to suit bespoke heating applications and tailored to customer preference. Oven trending is displayed for up to 48 hours and optional upgrades are available for alarm outputs.



## Sizes and Specifications

Genlab Reference Number		Capacity (litres)	Internal Dimensions (H x W x D cm)	External Dimensions (H x W x D cm)	Shelves / Positions	Wattage	Voltage	Weight (kg)
Horizontal with Twin Doors	LCO/250H/TDIG*	220	54 x 92 x 44	95 x 107 x 64	3..4	2500	230	96
	LCO/350H/TDIG*	320	54 x 92 x 64	95 x 107 x 84	3..4	2750	230	125
	LCO/425H/TDIG	450	76 x 92 x 64	104 x 136 x 84	4..5	3000	230	140
	LCO/500H/TDIG	535	91 x 92 x 64	120 x 136 x 84	5..7	3000	230	180
	LCO/650H/TDIG	645	91 x 92 x 77	129 x 157 x 98	5..7	6000	415	300
	LCO/750H/TDIG	750	106 x 92 x 77	144 x 157 x 98	5..8	6000	415	300
	LCO/850H/TDIG	865	122 x 92 x 77	160 x 157 x 98	5..9	6000	415	340
	LCO/1000H/TDIG	1005	142 x 92 x 77	180 x 157 x 98	5..11	6000	415	360
	LCO/1250H/TDIG	1280	142 x 122 x 74	180 x 187 x 95	5..11	6000	415	390
Vertical with Single Door	LCO/250V/TDIG	240	91 x 51 x 52	111 x 93 x 73	5..7	2500	230	90
	LCO/350V/TDIG	345	91 x 61 x 62	111 x 103 x 83	5..7	2750	230	120
	LCO/425V/TDIG	425	91 x 61 x 77	120 x 106 x 98	5..7	3000	230	150
	LCO/500V/TDIG	535	114 x 61 x 77	143 x 106 x 98	5..9	3000	230	165
	LCO/650V/TDIG	675	114 x 77 x 77	151 x 140 x 98	5..9	6000	415	280
	LCO/750V/TDIG	760	128 x 77 x 77	166 x 140 x 98	5..10	6000	415	300
	LCO/850V/TDIG	840	142 x 77 x 77	180 x 140 x 98	5..11	6000	415	320
	LCO/1000V/TDIG	1005	142 x 77 x 92	180 x 140 x 113	5..11	6000	415	340

\*Have base mount HMI  
Please see product datasheets for dimensional drawings

## Ordering

All units have CLAD interior with touch screen interface as standard. Where options are required simply add the option code to the original reference. e.g. **LCO/1250/TDIG** with stainless steel interior and audible alarm becomes **LCO/1250/TDIG/SS/AWA**. Contact sales for bespoke options.

## Option Codes

<b>SS</b>	Stainless Steel Chamber	<b>AWA</b>	Audible Warning	<b>EXP</b>	Explosion Relief Panels
<b>AP</b>	Access Ports	<b>STAND</b>	Stands	<b>3PH</b>	3 Phase Upgrade (<600L models only)
<b>EXT</b>	External Extraction System	<b>FSC</b>	Fan Speed Control	<b>10PRO</b>	10 menu x 8 profile (inc cyclic)
<b>ITL</b>	Integral Temperature Logger	<b>3PC</b>	3 Point Calibration	<b>1108</b>	Castor Wheels (250 - 350 models only)